



EC declaration of conformity

| For the | followin | g equipment |
|---------|----------|-------------|
|---------|----------|-------------|

Product Name: Switching Power Supplies

Model Designation: ULP-150-X (X=12,15,24,36,48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

RoHS Directive (2011/65/EU)

Energy-Related Products Directive (2009/125/EC) Implementing measure COMMISSION REGULATION(EC) No 1194/2012

Low Voltage Directive (2006/95/EC):

EN61347-1:2008+A1:2008+A2:2013/EN61347-2-13:2006 LVD certificate No: PSE102-1245-12

Electromagnetic Compatibility Directive (2004/108/EC):

EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

EN55015:2006+A1::2007+A2:2009

| Harmonic current | current EN61000-3-2:2006+A1:2009+A2:2009 | | | class C(≧60% load) | | |
|---------------------------------------|--|---------|------|--------------------|--|--|
| Voltage flicker | EN61000-3-3: 2008 | | | | | |
| EMS (Electro-Magnetic Susceptibility) | | | | | | |
| EN61547:2009 | | | | | | |
| ESD air | EN61000-4-2:2009 | Level 3 | 8KV | | | |
| ESD contact | EN61000-4-2:2009 | Level 2 | 4KV | | | |
| RF field susceptibility | EN61000-4-3:2006+A1:2008+A2:2010 | Level 2 | 3V/m | | | |

| EFT bursts | EN61000-4-4:2012 | Level 2 | 1KV/5KHz | |
|--------------------------|------------------|---------|---------------|----------------|
| Surge susceptibility | EN61000-4-5:2006 | Level 4 | 2KV/Line-Line | 4KV/Line-Earth |
| Conducted susceptibility | EN61000-4-6:2009 | Level 2 | 3V | |
| Magnetic field immunity | EN61000-4-8:2010 | Level 2 | 3A/m | |

Voltage dip, interruption EN61000-4-11:2004 >95% dip 0.5 periods 30% dip 25 periods >95% interruptions 250 periods Note:

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure.

For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies" (as available on

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains.

This Declaration is effective from serial number HB4xxxxxxx

Person responsible for marking this declaration:

Mean Well Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 248, Taiwan (R.O.C.)

(Manufacturer Address)

Johnny Huang/Senior Verification Engineer: (Name / Position)

(Signature) (Name / Position)

Ted Cheng/Product Manager:

Jun. 17th, 2014 Taiwan (Place) (Date)