

# (6

B B

# EC declaration of conformity

For the following equipment :

Product Name: AC/DC Switching Adaptor

Model Designation: GS120AX (X=12,15,20,24,48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :

### RoHS Directive (2011/65/EU) Low Voltage Directive (2006/95/EC) :

EN60950-1:2006+A11+A1+A12+A2

TUV certificate No : S50311813

| <b>Electromagnetic Compatibilit</b> | y Directive (2004/108/EC) : |
|-------------------------------------|-----------------------------|
|-------------------------------------|-----------------------------|

### EMI (Electro-Magnetic Interference)

Conducted emission / Radiated emission

| EN55022:2010                   | Class |
|--------------------------------|-------|
| EN55011:2009+A1:2010 (Group 1) | Class |
| EN61000-6-3:2007+A1:2011       |       |
| EN61204-3:2000                 |       |
|                                |       |

Harmonic current EN61000-3-2:2006+A1:2009+A2::2009

| Voltage flicker | EN61000-3-3:2008 |
|-----------------|------------------|
|                 |                  |

## EMS (Electro-Magnetic Susceptibility)

| EN55024:2010 EN61204      | -3:2000 EN61000-6-1:2007                 |               |                                      |
|---------------------------|--|---------------|--------------------------------------|
| ESD air                   | EN61000-4-2:2009                         | Level 3       | 8KV                                  |
| ESD contact               | EN61000-4-2:2009                         | Level 2       | 4KV                                  |
| RF field susceptibility   | EN61000-4-3:2006+A1:2008+A2:2010         | Level 2       | 3V/m                                 |
| EFT bursts                | EN61000-4-4:2012                         | Level 2       | 1KV/5KHz                             |
| Surge susceptibility      | EN61000-4-5:2006                         | Level 2       | 1KV/Line-Line                        |
| Surge susceptibility      | EN61000-4-5:2006                         | Level 3       | 2KV/Line-Earth                       |
| Conducted susceptibility  | EN61000-4-6:2009                         | Level 2       | 3V                                   |
| Magnetic field immunity   | EN61000-4-8:2010                         | Level 2       | 3A/m                                 |
| Voltage dip, interruption | EN61000-4-11:2004 >95% dip 0.5 periods 3 | 30% dip 25 pe | riods >95% interruptions 250 periods |

Note:

The power supply is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete system, the final equipment manufacturers must re-qualify EMC Directive on the complete system again.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

### Energy-Related Products Directive (2009/125/EC) :

Ecodesign requirements for no-load condition electric power consumption and average active efficiency of external power supplies EC No.278/2009

This Declaration is effective from serial number EB5xxxxxxx

Person responsible for marking this declaration :

Mean Well Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 248, Taiwan (Manufacturer Address)

Johnny Huang/Senior Verification Engineer : (Name / Position)

unna (Signature)

May. 25th, 2015

(Date)

Ted Cheng/Product Manager : (Name / Position)

(Signature)

| Taiwan  |
|---------|
| (Place) |